This page is created by "MM Linux User Group" 2005 Feb 01) What option is used with the useradd command to specify the user's home directory? A. -d B. -h C. -u D. -a Answer: A _____ 02) What switch is used with the usermod command to change a user's secondary groups? A. -G B. -group C. -d D. -U Answer: A ______ 03) Do changes to the inittab file require a reboot in order to take effect? A. No B. Yes Answer: A _____ 04) You want to repeat the last command you entered. How would you do this? A. # B. !! C. #1 D. ## Answer: B 05) What option can be used with the shutdown command to cancel a pending shutdown? A. shutdown -c B. shutdown -x C. shutdown -n D. shutdown -u

06) Which of the following are required in the /etc/passwd file when creating a user account?

Answer: A

A. login name B. userid

C. default group D. password age

Answer: A, B, C

(Choose all that apply)

E. minimum password length

07) You have just added the following line to your syslog.conf file: lpr.info /dev/console. But, line printer messages are not being sent to the console. What is most likely the problem?		
A. after modifying the syslog.conf file, the syslog daemon needs to be restarted. B. the entry is formatted incorrectly C. the syslog daemon reads it configuration information from the syslogd file		
Answer: A		
08) What run level represents basic multi-user?		
B. 0 C. 1 D. 5		
Answer: A		
09) What command be used to find the systems previous run level?		
A. runlevel B. level C. rlevel previous D. show level previous		
Answer: A		
10) What syslog.conf facility represents user authentication processes?		
A. auth B. proc C. user D. login		
Answer: A		
11) What syslog.conf facility represents the cron daemon?		
A. crond B. daemon C. cron D. crontab		
Answer: C		
12) Which of the following syslog identifiers represents the highest priority?		
A. notice B. warning C. error D. critical		
Answer: D		

13) Which of the following switches can be used with the tar command to find out the difference between two tar files?
Ac Bv Cd Dt
Answer: C
14) You want to add files to a previously created tar file. You want to replace existing files with newer files, how can you do this?
A. Use the append command B. Use the tar command with the -t switch C. Use the add command D. Use the tar command with the -u switch
Answer: D
15) What syslog.conf facility represents kernel processes?
A. user B. proc C. daemon D. kern
Answer: D
16) You want to view a listing of previously entered commands. What command would you use?
A. hist B. histfile C. showbuff D. history
Answer: D
17) Which of the following syslog identifiers represents the highest priority?
A. alert B. error C. critical D. emerg
Answer: D
18) You want to uninstall lilo. Which of the following would you do to accomplish this?
A. lilo -u B. remove lilo C. uninstall lilo D. lilo -r
Answer: A

19) Linux is a(n)	operating system, meaning the source code is freely available.
A. Open sourced B. User licensed C. Closed source D. Open binary	
Answer: A	
20) DNS provides	
A. NETBIOS name B. host name C. MAC address	
Answer: B	
	grace days after a password expires before an account becomes disabled.
A. Use the useradd comman B. Check the delay option in C. Edit the user's user.conf f D. Use the useradd comman	n user admin ĭle
Answer: A	
22) You had a contractor co	me into your company. You originally set his account to expire after thirty age this. How can you do this?
A. usermod -e B. usermod -a C. usermod -x D. usermod -d	
Answer: A	
	ocess /etc/myprocess run when the system enters run level 3. ab entries would accomplish this?
A. 5:3:once:/etc/myprocess B. 3:4:once:/etc/myprocess C. once:3:4:/etc/myprocess D. once:5:3:/etc/myprocess	
Answer: A	
24) What option can be used the system will be shut down	d with the shutdown command to send a warning message alerting users that n?
A. shutdown -k B. shutdown -w C. shutdown -a D. shutdown -c	
Answer: A	

25) Which of the following syslog.conf entries would cause kernel error messages to be sent to the system console?
A. kern warning console B. kern.error console C. kern.warning /dev/console D. kern error console
Answer: C
26) What run level represents multi-user?
A. 3 B. 0 C. 1 D. 5
Answer: A
27) What syslog.conf facility represents miscellaneous daemons?
A. misc B. proc C. kern D. daemon
Answer: D
28) What syslog.conf facility represents Unix to Unix copy?
A. ucp B. copy C. uucp D. uuc
Answer: C
29) Which of the following syslog identifiers represents the highest priority?
A. info B. warning C. notice
Answer: B
30) You want to add information to a previously created tar file. How would you do this?
A. Use the tar command with the -a switch B. Use the append command C. Use the add command D. Use the tar command with the -r switch
Answer: D

31) What syslog.conf facility represents user processes?
A. auth
B. proc
C. user
D. u
Answer: C
32) What command can be used to print out system boot messages?
A. bootm
B. bmsg
C. messages
D. dmesg
Answer: D
33) You want to set a 30 second delay before your system boots to the default kernel. Which of the following command lines would do this?
A. lilo -t 30
B. lilo -d 30
C. lilo delay 30
D. lilo 30
Answer: B
34) What command can be used to show all variables?
A. set
B. varlist
C. show var
D. show
Answer: A
35) What option is used with the useradd command to specify the user's user id?
Au
Bs
Cui
Did
Answer: A
36) You are adding a new user. You want to create the user's home directory only if the directory does no exist. Which of the following would accomplish this?
A. useradd -m
B. useradd -h -y
C. useradd -u
D. useradd -h
Answer: A

37) Which of the following can be used to switch your system to run level 1?
A. init 1 B. inittab 1 C. rlevel 1 D. level 1
Answer: A
38) You want to do a system shutdown, but you dont want the shutdown to occur immediately. You want the system to wait 60 seconds before doing the shutdown. What option can be used with the shutdown command to wait 60 seconds before starting the shutdown?
A. shutdown -t 60 B. shutdown -w 1 C. shutdown -c 60 D. shutdown -t 1
Answer: A
39) What run level represents administration mode?
A. 0 B. 1 C. 6 D. 5
Answer: B
40) What file does init processes use as its control file?
A. /etc/inittab B. /etc/proc C. /etc/init D. /etc/initproc
Answer: A
41) What syslog.conf facility is used to create timestamps in log files?
A. mark B. stamp C. time D. tstamp
Answer: A
42) Which of the following commands can be used to create a tar archive file in verbose mode?
A. tar -v B. tar -cvf C. tar -c D. tar -vf
Answer: B

43) What is the name of the configuration file used by the syslog daemon?
A. syslog.conf B. syslogd C. slog.conf D. system.conf
Answer: A
44) What lilo.conf parameter will cause the root file system to be mounted read only?
A. no-write B. read C. no-right D. read-only
Answer: D
45) Which of the following syslog.conf entries would cause kernel error messages to be sent to the system console?
A. kern warning console B. kern.error console C. kern.warning /dev/console D. kern error console
Answer: C
46) What option is used with the useradd command to specify the user's login shell?
As Bl Cu Dsh
Answer: A
47) Which of the following can be used to change a user's home directory?
A. usermod -d B. usermod -h C. usermod -u D. usermod -c
Answer: A
48) You want to have the process /etc/myprocess to run when the system enters run level 2. You want the system to wait until the process completes. Which of the following inittab entries would accomplish this?
A. 7:2:wait:/etc/myprocess B. 2:7:wait:/etc/myprocess C. wait:2:7:/etc/myprocess D. wait:7:2:/etc/myprocess
Answer: A

49) Which of the following syslog.conf entries would cause kernel warning messages to be sent to the system console?
A. kern.console warning B. kern.warning /dev/console C. kern.warning.console D. kern warning console
Answer: B
50) You want to repeat a command that began with the letters 'ab'. How would you do this?
A. !ab B. list ab C. #ab D. show ab
Answer: A
51) What syslog.conf facility represents login processes?
A. proc B. login C. user D. auth
Answer: D
52) What option can be used with the shutdown command to cancel a pending shutdown?
A. shutdown -c B. shutdown -x C. shutdown -n D. shutdown -u
Answer: A
53) Which of the following commands can be used to extract a tar file?
A. tar -vf B. tar -xvf C. tar -e D. tar -v
Answer: B
54) Which of the following Linux packages can be used for web caching?
A. qmail B. squid C. apache D. samba
Answer: B

55) What lilo.conf parameter is used to specify what device should be mounted as root by default?
A. root B. drive C. mntroot D. mount
Answer: A
56) You want to find the full path of a certain command. How would you do this?
A. By using the 'where' command B. By using the 'path' command C. By using the 'which' command
Answer: C
57) You want a user's account to expire in ten days. What option used with the useradd command will allow you to do this?
Ae Bu Cd Dt
Answer: A
58) Which of the following can be used to switch your system to run level 3?
A. init 3 B. rlevel 3 C. level 3 D. inittab 3
Answer: A
59) Which of the following syslog.conf entries would cause mail error messages to be sent to the system console?
A. mail error console B. mail.err /dev/console C. mail. error console D. mail.err.console
Answer: B
60) What command can be used to find the current run level?
A. runlevel B. level C. show level D. rlevel
Answer: A

61) Which of the following syslog identifiers represents the highest priority?
E. alert F. error G. critical H. emerg
Answer: D
62) What daemon controls the syslog?
A. syslog B. syslogd C. logd D. sys
Answer: B
63) Which lilo.conf parameter will specify the amount of time the system will wait before booting to the default image?
A. wait B. delay C. pause D. default
Answer: B
64) What switch is used with the useradd command to specify a user's initial group?
Ag Bi Cu Dig
Answer: A
65) What option can be used with the shutdown command to skip fsck on reboot?
A. shutdown -f B. shutdown -o C. shutdown -r D. shutdown -s
Answer: A
66) What run level represents a power down?
A. 5 B. 0 C. 1 D. 4
Answer: B

67) What syslog.conf facility represents the line printer?
A. ptr
B. linep
C. lpr D. lprinter
Answer: C
68) Which daemon will send kernel alert messages?
A. alertd
B. smtpd
C. krnld
D. syslogd
Answer: D
69) What syslog.conf facility represents mail processes?
A. proc
B. daemon
C. mail D. smtp
D. Shitp
Answer: C
70) What syslog.conf facility represents user processes?
A. auth
B. proc
C. user D. u
Answer: C
71) What command can be used to cause changes to the inittab file to take effect without a system reboot
A. init q
B. init r
C. inittab r
D. inittab q
Answer: A
72) What option can be used with the shutdown command to reboot the system?
A. shutdown -r
B. shutdown -y
C. shutdown -c
D. shutdown -b
Answer: A

73) What run level represents a system reboot?
A. 6 B. 1 C. 2 D. 5
Answer: A
74) What syslog.conf facility represents Usenet news?
A. usenet B. news C. uunet D. net
Answer: B
75) You want to find out what files are contained in a tar file. How would you do this?
A. Use the tar command with the -t switch B. Use the tar command with the -r switch C. Use the grep command D. Use the find command
Answer: A
76) What syslog.conf facility represents httpd processes?
A. http B. daemon C. smtp D. proc
Answer: B
77) You want to repeat command number 3 in your history. How would you do this?
A. repeat 3 B. !3 C. show 3 D. #3
Answer: B
78) What lilo option will list the name and location of available kernels?
Aq Bk Cv D1
Answer: A

79) What lilo.conf parameter is used to specify vga text mode?
A. vgatext B. svga C. vga D. vtm
Answer: C
80) You want to set a script to run when your Linux system reboots. What lilo option should you use?
AR BS CT DL
Answer: A